

	Basic dimensions L/D	Unmated tolerance TOL																																																																											
0.5-6	±0.1																																																																												
>6-30	±0.2																																																																												
>30-120	±0.3																																																																												
>120-400	±0.5																																																																												
>400-1000	±0.8																																																																												
>1000-2000	±1.2																																																																												
>2000-4000	±2																																																																												
Round/Chamfering R/C	Unmated tolerance TOL																																																																												
0.5-3	±0.2																																																																												
>3-6	±0.5																																																																												
>6	±1.0																																																																												
Short side length LESS	Unmated tolerance TOL																																																																												
>0-10	±1																																																																												
>10-50	±0.5																																																																												
>50-120	±0.3																																																																												
>120-400	±0.15																																																																												
>400	±0.1																																																																												
			CSAG-K320S (SUSPENSION 2:1) Permanent Magnet Synchronous Gearless Traction Machine																																																																										
			<table><tr><td>Model</td><td>ØD</td><td>Groove profile</td><td>Ød</td><td>α</td><td>β</td><td>P</td></tr><tr><td>CSAG-K320S</td><td>Ø320</td><td>U</td><td>8</td><td>35°</td><td>96°</td><td>12</td></tr></table>															Model	ØD	Groove profile	Ød	α	β	P	CSAG-K320S	Ø320	U	8	35°	96°	12																																														
Model	ØD	Groove profile	Ød	α	β	P																																																																							
CSAG-K320S	Ø320	U	8	35°	96°	12																																																																							
			<table><tr><td colspan="2">Spec.</td><td>Load</td><td>Speed</td><td>Height</td><td>Torque</td><td>Sheave Dia.</td><td>Rope Dia.</td><td>Groove</td><td>Distance Between Grooves</td><td>Power</td><td>Rated Voltage</td><td>Rated Current</td><td>Rated Frequency</td><td>Rated Speed</td></tr><tr><td></td><td></td><td>kg</td><td>m/s</td><td>m</td><td>Nm</td><td>mm</td><td>mm</td><td>pcs</td><td>mm</td><td>kW</td><td>V</td><td>A</td><td>Hz</td><td>rpm</td></tr><tr><td colspan="2">CSAG-K320S-1600-1.0</td><td>1600</td><td>1</td><td>≤50</td><td>860</td><td>320</td><td>8</td><td>10</td><td>12</td><td>10.7</td><td>380</td><td>24.6</td><td>23.8</td><td>119</td></tr><tr><td colspan="2">CSAG-K320S-1600-1.6</td><td>1600</td><td>1.6</td><td>≤80</td><td>860</td><td>320</td><td>8</td><td>10</td><td>12</td><td>17.1</td><td>380</td><td>43.1</td><td>38.2</td><td>191</td></tr></table>															Spec.		Load	Speed	Height	Torque	Sheave Dia.	Rope Dia.	Groove	Distance Between Grooves	Power	Rated Voltage	Rated Current	Rated Frequency	Rated Speed			kg	m/s	m	Nm	mm	mm	pcs	mm	kW	V	A	Hz	rpm	CSAG-K320S-1600-1.0		1600	1	≤50	860	320	8	10	12	10.7	380	24.6	23.8	119	CSAG-K320S-1600-1.6		1600	1.6	≤80	860	320	8	10	12	17.1	380	43.1	38.2	191
Spec.		Load	Speed	Height	Torque	Sheave Dia.	Rope Dia.	Groove	Distance Between Grooves	Power	Rated Voltage	Rated Current	Rated Frequency	Rated Speed																																																															
		kg	m/s	m	Nm	mm	mm	pcs	mm	kW	V	A	Hz	rpm																																																															
CSAG-K320S-1600-1.0		1600	1	≤50	860	320	8	10	12	10.7	380	24.6	23.8	119																																																															
CSAG-K320S-1600-1.6		1600	1.6	≤80	860	320	8	10	12	17.1	380	43.1	38.2	191																																																															
			<table><tr><td colspan="2">Part Name</td><td colspan="2">Drawing No</td></tr><tr><td colspan="2">Outline drawing</td><td colspan="2">A210120004</td></tr><tr><td colspan="2">Model</td><td colspan="2">Material</td></tr><tr><td colspan="2">CSAG-K320S-1600kg</td><td colspan="2"></td></tr><tr><td colspan="2">Scale</td><td colspan="2"></td></tr><tr><td colspan="2">1: 1</td><td colspan="2"></td></tr><tr><td colspan="2">Total pages</td><td colspan="2">Page</td></tr><tr><td colspan="2">1</td><td colspan="2">1</td></tr><tr><td colspan="2">Weight</td><td colspan="2"></td></tr></table>															Part Name		Drawing No		Outline drawing		A210120004		Model		Material		CSAG-K320S-1600kg				Scale				1: 1				Total pages		Page		1		1		Weight																											
Part Name		Drawing No																																																																											
Outline drawing		A210120004																																																																											
Model		Material																																																																											
CSAG-K320S-1600kg																																																																													
Scale																																																																													
1: 1																																																																													
Total pages		Page																																																																											
1		1																																																																											
Weight																																																																													
			<table><tr><td colspan="2">Signature</td><td colspan="2">Date</td><td colspan="2">Signature</td><td colspan="2">Date</td></tr><tr><td colspan="2">CHK</td><td colspan="2"></td><td colspan="2">TBC</td><td colspan="2"></td></tr><tr><td colspan="2">DSG</td><td colspan="2"></td><td colspan="2">APD</td><td colspan="2"></td></tr></table>															Signature		Date		Signature		Date		CHK				TBC				DSG				APD																																							
Signature		Date		Signature		Date																																																																							
CHK				TBC																																																																									
DSG				APD																																																																									
			<table><tr><td colspan="2">Person in charge</td><td colspan="2">Date</td><td colspan="2">First drawing date</td><td colspan="2">2025. 6. 17</td></tr></table>															Person in charge		Date		First drawing date		2025. 6. 17																																																					
Person in charge		Date		First drawing date		2025. 6. 17																																																																							
			<table><tr><td colspan="2">Change the content</td><td colspan="2">Version No.</td><td colspan="2">Mark</td><td colspan="2">NO.</td></tr></table>															Change the content		Version No.		Mark		NO.																																																					
Change the content		Version No.		Mark		NO.																																																																							
			CEG Motor (SUZHOU) Co., LTD																																																																										

NAME: CSAG (SUZHOU) Co., LTD., to file and contains data ownership, can only be used in the scope of the company for the purpose: Without prior written authorization, shall not copy or disclose all and part information; And must be returned in time related information and copy to CSAG (SUZHOU) Co., LTD.,